

lightnet

Cubic-M2

Recessed mounted luminaire (trimless) for ceilings, mounting brackets incl - Direct light distribution

Article code: CM2AWE-830H-Q612



Illustrations may only be similar and serve as an orientation.





Cubic-M2. LED. Recessed mounted luminaire for frameless installation in plasterboard ceilings. Mounting brackets included. Luminaire body with increased stability for installation. Surface finish Snow White. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. Switchable. LxWxH (square). L=612mm. W=612mm. H=

107mm. High-power current. 7424lm. 65W. 6,5kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Cubic-M2

Recessed mounted luminaire (trimless) for ceilings, mounting brackets incl - Direct light



Article code: CM2AWE-830H-Q612

Customer / Project: _____

Note: _____

Productname	Cubic-M2
Lamp	LED
Installation Type	Recessed mounted luminaire (trimless) for ceilings, mounting brackets incl
Surface finish	Snow White
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Switchable
Length L/Diameter D (mm)	L=612mm
Width W (mm)	W=612mm
Height H (mm)	H=107mm
Current/Power	High-Power
Luminous Flux	7424lm
Power consumption	65W
Degree of protection	IP20
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	6,5kg

