


Beam Me Up-X1

Surface mounted luminaire - Direct/indirect light distribution Article code: MX1AWE-830M-D1200-W



Illustrations may only be similar and serve as an orientation.




Beam Me Up-X1. LED. Design surface mounted luminaire for ceiling mounting with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Snow White. Direct light distribution and indirect lighting corona. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=16. Reflector: Snow White. Switchable. DxH

(round). D=1200mm. H=350+60mm. Medium-power current. 18204lm. 177W. 22,5kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Beam Me Up-X1

Surface mounted luminaire - Direct/indirect light distribution

Article code: MX1AWE-830M-D1200-W



Customer / Project: _____

Note: _____

Productname	Beam Me Up-X1
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Snow White
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Reflector Colour Inside	Reflector: Snow White
Control	Switchable
Length L/Diameter D (mm)	D=1200mm
Height H (mm)	H=350+60mm
Current/Power	Medium-Power
Luminous Flux	18204lm
Power consumption	177W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
UGR	UGR<=16
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	22,5kg

