

Midpoint-W7

Spotlight for wall surface mounting - Direct/indirect light distribution

Article code: PW7AWE-930AM-BK



Illustrations may only be similar and serve as an orientation.

Midpoint-W7. LED. Spotlight for wall surface mounting. Luminaire body made of high-quality aluminum profile. Surface finish Snow White. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >90. Reflector with beam angle SPOT 10°. Reflector: Jet Black. XICATO/ARTIST (CRI>97). Clear Cover. Switchable. DxHxW (spots). D=90mm. W=105mm. H=

320mm. Medium-power current. 2180lm. 38W. 1,7kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG1 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Midpoint-W7

Spotlight for wall surface mounting -
Direct/indirect light distribution



Article code: PW7AWE-930AM-BK

Customer / Project: _____

Note: _____

Productname	Midpoint-W7
Lamp	LED
Installation Type	Spotlight for wall surface mounting
Surface finish	Snow White
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>90
Reflector Beam Angle	Reflector: SPOT 10°
Reflector Colour Inside	Reflector: Jet Black
LED-Module Type	XICATO/ARTIST (CRI>97)
Cover	Clear Cover
Control	Switchable
Length L/Diameter D (mm)	D=90mm
Width W (mm)	W=105mm
Height H (mm)	H=320mm
Current/Power	Medium-Power
Luminous Flux	2180lm
Power consumption	38W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	9 30 / 3 3 9
Photobiological class	RG1 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	1,7kg

