

## Matric-JX

Wall mounted luminaire - Indirect light distribution

Article code: LJXAW-840H-Lxxxx



Illustrations may only be similar and serve as an orientation.



Matric-JX. LED. Wall mounted luminaire. Luminaire body made of high-quality aluminum profile. Surface finish Snow White. Indirect only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for reduced luminance in office areas. Switchable. according to drawing. LxWxH (rectangular). Special length L=xxxxmm. W=75mm. H=45mm. High-power

current. 2020lm/m. 34W/m. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25° C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

## Matric-JX

Wall mounted luminaire - Indirect light distribution

Article code: LJXAW-840H-Lxxxx



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Matric-JX
Lamp	LED
Installation Type	Wall mounted luminaire
Surface finish	Snow White
Light characteristics	Indirect light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Switchable
Length L/Diameter D (mm)	Special length L=xxxxmm
Width W (mm)	W=75mm
Height H (mm)	H=45mm
Current/Power	High-Power
Luminous Flux	2020lm/m
Power consumption	34W/m
Degree of protection	IP20
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Other	according to drawing

