lightnet

Matric-G7

Pendant luminaire - Direct light distribution

Article code: LG7LWL-830E-L1335-YW



Illustrations may only be similar and serve as an orientation.


Matric-G7. LED. Pendant luminaire. Luminaire body made of high-quality aluminum profile. Surface finish Snow White. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Lens Louvre: precision lenses with louvre. High glare limitation, compatible for office applications. UGR<=19. Reflector: Snow White. Dimmable DALI. LxWxH (light line). L= 1335mm. W=81mm. H=40mm. Y-cord suspension with power supply cable and ceiling rose (Set). Pendant length max 1500mm. Power supply: transparent. Ceiling rose: Matching luminaire`s surface colour. Low-power current. 2029lm. 16W. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

lightnet

Matric-G7

Pendant luminaire - Direct light distribution





Article code: LG7LWL-830E-L1335-YW

Customer	/ Project	•
Customer	/ Project	•

Note:

Productname Lamp Installation Type Surface finish Light characteristics Colour temperature Colour Rendering Index (CRI) Optical system Reflector Colour Inside Control Length L/Diameter D (mm) Width W (mm) Height H (mm) Current/Power Luminous Flux Power consumption Suspension Ceiling rose colour Pendant length (mm) Degree of protection Cable Colour LED lifetime UGR

Photometric code

Indoor/Outdoor

Photobiological class

Matric-G7 I FD Pendant luminaire Snow White Direct light distribution 3000K CRI>80 Lens Louvre **Reflector: Snow White** Dimmable (DALI) L=1335mm W=81mm H=40mm Low-Power 2029lm 16W Y-susp. (Set) Ceiling rose: Matching luminaire`s surface colour Pendant length max 1500mm IP20 Power supply: transparent L90B10 (tq 25°C) = 50.000h UGR<=19 830/339 RG0 (EN62471) Indoor: ta [ambient] max. 25°C

IP20 E 2032/00/ 176-275V IK RG0 S 100/ 176-27