

Ringo Star-GY Acoustic Oblong

Acoustic pendant luminaire - Direct light distribution

Article code: RGYCWL-840H-O62-K-GF



Illustrations may only be similar and serve as an orientation.



Ringo Star-GY Acoustic Oblong. LED. Acoustic pendant luminaire. Luminaire body made of high-quality aluminum profile. Surface finish Snow White. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal Flex Diffuser. Dimmable DALI. L/DxWxH (oval). L/D=2450/600mm. W=40mm. H=40mm. Cord suspension for parallel installation with power supply cable and ceiling rose (Set). Pendant length max 4000mm. Power supply: transparent. Ceiling rose: Matching luminaire's surface colour. High-power

current. 11730lm. 121W. Binning initial <= MacAdam 3. Internal sound absorber for a wide frequency spectrum, to reduce the reverberation time in Green Fabric. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Ringo Star-GY Acoustic Oblong

Acoustic pendant luminaire - Direct light distribution

Article code: RGYCWL-840H-O62-K-GF



Customer / Project: _____

Note: _____

Productname	Ringo Star-GY Acoustic Oblong
Lamp	LED
Installation Type	Acoustic pendant luminaire
Surface finish	Snow White
Light characteristics	Direct light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal Flex Diffuser
Control	Dimmable (DALI)
Length L/Diameter D (mm)	L/D=2450/600mm
Width W (mm)	W=40mm
Height H (mm)	H=40mm
Current/Power	High-Power
Luminous Flux	11730lm
Power consumption	121W
Suspension	Parallel susp. (Set)
Ceiling rose colour	Ceiling rose: Matching luminaire`s surface colour
Pendant length (mm)	Pendant length max 4000mm
Acoustic absorber	Absorber (Green Fabric)
Degree of protection	IP20
Cable Colour	Power supply: transparent
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C

