

# lightnet

## Ringo Star-PY

Pendant luminaire - Direct/indirect light distribution

Article code: 1RPYCWE-830M-D2500-K



Illustrations may only be similar and serve as an orientation.





Ringo Star-PY. LED. Pendant luminaire made with 1.625" profile width. Direct/indirect light distribution. Opal Flex Diffuser. Surface finish Snow White. Switchable. Color Rendering Index (CRI): >80. Color temperature: 3000K (Warm White). Medium-power current. DxHxW (round). D= 98,4". W=1,6". H=1,6". Cord suspension for parallel installation with power supply cable and canopy (Set). Pendant length max 158". Power supply: transparent. Canopy matching

luminaire`s surface color with integrated driver. 25105lm. 288W. Binning initial <= MacAdam 3. 37,7lbs. IP20. Protection class I. cETLus. IK02. 120-277V. 50-60 Hz. RG0 (EN62471). A minimum LED lifetime of 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements. 5 years warranty. Manufacturer: Lightnet USA Inc

Ringo Star-PY

Pendant luminaire - Direct/indirect light distribution



Article code: 1RPYCWE-830M-D2500-K

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Ringo Star-PY
Lamp	LED
Installation Type	Pendant luminaire
Light characteristics	Direct/indirect light distribution
Optical system	Opal Flex Diffuser
Surface finish	Snow White
Control	Switchable
Color Rendering Index (CRI)	CRI>80
Color temperature	3000K
Current/Power	Medium-Power
Length L/Diameter D (in)	D=98,4"
Width W (in)	W=1,6"
Height H (in)	H=1,6"
Luminous Flux	25105lm
Power consumption	288W
Voltage	120-277V
Degree of protection	IP20
Suspension	Parallel cord susp (Set) Pendant length max 158"
LED lifetime	L85/50,000h (tq 25°C)
Certification	cETLus
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (lbs)	37,7lbs

