


## Caleo-X6

Surface mounted luminaire - Direct/indirect light distribution    Article code: 1AX6AWE-827M-Q300-B



Illustrations may only be similar and serve as an orientation.



Caleo-X6. LED. Surface-mounted luminaire for walls and ceilings. Surface finish Snow White. Direct light distribution and indirect lighting corona. Color temperature: 2700K (Soft White). Color Rendering Index (CRI): >80. Microprismatic screen for reduced luminance in office areas. UGR<=19. Reflector: Jet Black. Switchable. LxWxH (square). L=11,8". W=11,8". H=1"+1,4". Medium-power current. 1861lm. 17W.

4,9lbs. Binning initial <= MacAdam 3. IP20. Protection class I. cETLus pending. IK02. 120-277V. 50-60 Hz. RG0 (EN62471). A minimum LED lifetime of 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements. 5 years warranty. Manufacturer: Lightnet USA Inc

Caleo-X6

Surface mounted luminaire - Direct/indirect light distribution

Article code: 1AX6AWE-827M-Q300-B



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Caleo-X6
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Snow White
Light characteristics	Direct/indirect light distribution
Color temperature	2700K
Color Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
UGR	UGR<=19
Reflector Color Inside	Reflector: Jet Black
Control	Switchable
Length L/Diameter D (in)	L=11,8"
Width W (in)	W=11,8"
Height H (in)	H=1"+1,4"
Current/Power	Medium-Power
Luminous Flux	1861lm
Power consumption	17W
Voltage	120-277V
Degree of protection	IP20
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
LED lifetime	L85/50,000h (tq 25°C)
Certification	cETLus pending
Weight (lbs)	4,9lbs

