

Ringo Star G3/P3 | System 60mm Suspended



DE LED-Pendelleuchte. Direkt-indirekt oder rein direktstrahlend. Leuchtenkörper aus Aluminiumprofil mit 60mm Profildbreite. 13 verschiedene Durchmesser von 600mm bis 8000mm. Oberfläche weiß, silber, graphit, schwarz, champagner oder kupferfarben lackiert. Weitere Oberflächenoptionen siehe Lightnet-Surface-Collection oder RAL nach Wahl. Microprismenoptik mit optimierter Blendungsbegrenzung speziell für Office-Anwendungen. Satinierter Opaldiffusor für Allgemeinbeleuchtung mit max. Transmissionsgrad und homogener Lichtpunktauflösung. Konverter in Leuchtengehäuse integriert, wahlweise einfach schaltbar oder stufenlos dimmbar (DALI, Touch-Dim, Casambi). Farbtemperatur 2200K, 2700K, 3000K, 3500K, 4000K, 6500K oder Tunable White (2700-6500K). Binning initial $\leq$ MacAdam 3. Farbwiedergabe CRI>80, CRI>90 oder Full Spectrum. Stufenlos höhenverstellbare Zentral-, Parallel- oder Disc-Seilabhängung mit transparent ummantelter Zuleitung. Lackierung Baldachin passend Leuchtenkörper.


EN LED pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body made of 60mm wide aluminium profile. 13 different diameters from 600mm to 8000mm. Surface white, silver, graphite, black, champagne or copper coated. For further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Driver integrated into luminaire housing, optionally switchable or dimmable (DALI, Touch-Dim, Casambi). Colour temperature 2200K, 2700K, 3000K, 3500K, 4000K, 6500K or Tunable White (2700-6500K). Binning $\leq$ MacAdam 3. Colour rendering CRI>80, CRI>90 or Full Spectrum. Height-adjustable central, parallel or disc cord suspension with transparent power supply cable. Colours ceiling rose match to luminaire body.

R P3 O S L - 8 30 H-D1500-U


Product Family	R: Ringo Star
Type	P3: Direct-Indirect, G3: Direct only
Optical System	A: Microprismatic, O: Opal Diffuser
Surface Finish	W: Snow White, V: Ivory White, S: Radiant Silver, U: Urban Graphite, B: Jet Black, H: Anodic Champagne, K: Satin Copper
Control Gear	E: On/Off, L: DALI, H: Touch-Dim, C: Casambi, U: Separately Dimmable DALI, 6: DALI DT6 for TW, 8: DALI DT8 for TW
Colour Rendering	8: CRI>80, 9: CRI>90, F: Full Spectrum [except 2200K]
Colour Temperature	22: 2200K, 27: 2700K, 30: 3000K, 35: 3500K, 40: 4000K, 65: 6500K, TW: Tunable White 2700-6500K [D1500-D8000]
Power	M: Medium Power, H: High Power
Size	Luminaire Diameter in mm: D600, D900, D1200, D1500, D2000, D2500, D3000, D3500, D4000, D5000 D6000, D7000, D8000
Suspension	K: Parallel Suspension, U: Central Suspension [D600-D2000], D: Disc Suspension [D600-D2000]
On Request	Emergency Module [D1500-D8000], Midpin Spotlights




Microprismatic | Direct-Indirect




Microprismatic | Direct



Opal Diffuser | Direct-Indirect



Opal Diffuser | Direct



D mm	Lumen/Watt Medium Power
600	6730lm/61W
900	10750lm/100W
1200	14100lm/128W
1500	18940lm/168W
2000	23670lm/214W
2500	29440lm/267W
3000	35200lm/320W
3500	42400lm/385W
4000	49300lm/454W
5000	59800lm/546W
6000	70400lm/639W
7000	79900lm/734W
8000	94100lm/862W


D mm	Lumen/Watt Medium Power	Lumen/Watt High Power
600	2950lm/36W	4050lm/51W
900	4730lm/60W	6160lm/78W
1200	6170lm/76W	8600lm/112W
1500	8300lm/100W	10900lm/137W
2000	10400lm/127W	13650lm/173W
2500	13500lm/164W	17750lm/223W
3000	16600lm/200W	21850lm/273W
3500	19800lm/240W	26000lm/323W
4000	22760lm/280W	29900lm/380W
5000	27850lm/342W	36900lm/459W
6000	33200lm/400W	43700lm/546W
7000	37340lm/462W	49150lm/626W
8000	43570lm/534W	57350lm/725W

D mm	Lumen/Watt Medium Power
600	6980lm/61W
900	11150lm/100W
1200	14650lm/128W
1500	19650lm/168W
2000	24560lm/214W
2500	30600lm/267W
3000	36600lm/320W
3500	44100lm/385W
4000	51300lm/454W
5000	62150lm/546W
6000	73300lm/639W
7000	83100lm/734W
8000	97800lm/862W


D mm	Lumen/Watt Medium Power	Lumen/Watt High Power
600	3200lm/36W	4400lm/51W
900	5130lm/60W	6690lm/78W
1200	6700lm/76W	9350lm/112W
1500	9000lm/100W	11860lm/137W
2000	11260lm/127W	14800lm/173W
2500	14640lm/164W	19260lm/223W
3000	18000lm/200W	23700lm/273W
3500	21470lm/240W	28200lm/323W
4000	24700lm/280W	32500lm/380W
5000	30200lm/342W	40100lm/459W
6000	36000lm/400W	47400lm/546W
7000	40530lm/462W	53350lm/626W
8000	47300lm/534W	62200lm/725W

Lumen Values: Luminaire luminous flux at 4000K/CRI>80. Other configurations on request.

Parallel Suspension



Central Suspension



Disc Suspension



Midpin Spotlight XP
770lm/10W/Ø40mm



W Snow White



S Radiant Silver



U Urban Graphite



B Jet Black



H Anodic Champagne



K Satin Copper