Plank Y4/X4 | Surface



DE LED-Anbauleuchte für Wand- oder Deckenmontage. Direktstrahlend mit indirekter Lichtkorona oder rein direktstrahlend. Leuchtenkörper aus Aluminiumprofil mit 25mm Bauhöhe. Oberfläche weiß, graphit, silber, schwarz, champagner oder kupferfarben lackiert. Weitere Oberflächenoptionen siehe Lightnet-Surface-Collection oder RAL nach Wahl. Microprismenoptik aus Spezialacrylglas mit optimierter Blendungsbegrenzung für Office-Anwendungen. Satinierter Opaldiffusor für Allgemeinbeleuchtung mit max. Transmissionsgrad und homogener Lichtpunktauflösung. Konverter in Leuchtengehäuse integriert, wahlweise einfach schaltbar oder stufenlos dimmbar (DALI, Touch-Dim, Casambi). Farbtemperatur 2200K, 2700K, 3000K, 3500K, 4000K, 6500K oder Tunable White (2700-6500K). Binning initial ≤ MacAdam 3. Farbwiedergabe CRI>80, CRI>90 oder Full Spectrum. Auf Anfrage: Integration von Stromschienen und Strahlern, Notlichtkomponenten, Sensortechnologie.


EN LED surface-mounted luminaire for walls or ceilings. Direct and indirect light distribution or direct only light distribution. Luminaire body made of 25mm high aluminium profile. Surface white, graphite, silver, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen made of special acrylic glass with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Driver integrated into luminaire housing, optionally switchable or dimmable (DALI, Touch-Dim, Casambi). Colour temperature 2200K, 2700K, 3000K, 3500K, 4000K, 6500K or Tunable White (2700-6500K). Binning≤ MacAdam 3. Colour rendering CRI>80, CRI>90 or Full Spectrum. On request: Integration of tracks and spotlights, emergency lighting components, sensor technology.

J X4 A W E-8 30 M-L1210

Product Family	**J**: Plank
Type	**X4**: Direct-Indirect, **Y4**: Direct only
Optical System	**A**: Microprismatic, **O**: Opal Diffuser
Surface Finish	**W**: Snow White, **S**: Radiant Silver, **U**: Urban Graphite, **B**: Jet Black, **H**: Anodic Champagne, **K**: Satin Copper **E**:
Control Gear	On/Off, **L**: DALI, **H**: Touch-Dim, **C**: Casambi, **6**: DALI DT6 for TW, **8**: DALI DT8 for TW
Colour Rendering	**8**: CRI>80, **9**: CRI>90, **F**: Full Spectrum [except 2200K]
Colour Temperature	**22**: 2200K, **27**: 2700K, **30**: 3000K, **35**: 3500K, **40**: 4000K, **65**: 6500K, **TW**: Tunable White 2700-6500K
Power	**M**: Medium Power, **H**: High Power
Size	Luminaire length in mm: **L920**, **L1210**, **L1500**, **L1800**


IP20 · ~220-240V · 50-60 Hz · IK 02 · RG0 · ≤3 MacAdam · Medium Power L85B10 50.000h · High Power L80B10 50.000h · CE · UKCA

Microprismatic | Direct-Indirect




L mm	Lumen/Watt Medium Power	Lumen/Watt High Power
920	2840lm/24W	4530lm/38W
1210	3790lm/33W	6030lm/53W
1500	4740lm/40W	7540lm/64W
1800	5690lm/47W	9050lm/76W

Microprismatic | Direct




L mm	Lumen/Watt Medium Power	Lumen/Watt High Power
920	1340lm/13W	2130lm/21W
1210	1790lm/17W	2840lm/27W
1500	2240lm/20W	3550lm/33W
1800	2690lm/24W	4260lm/39W

Opal Diffuser | Direct-Indirect




L mm	Lumen/Watt Medium Power	Lumen/Watt High Power
920	2750lm/24W	4380lm/38W
1210	3670lm/33W	5830lm/53W
1500	4580lm/40W	7290lm/64W
1800	5500lm/47W	8750lm/76W

Opal Diffuser | Direct



L mm	Lumen/Watt Medium Power	Lumen/Watt High Power
920	1250lm/13W	1980lm/21W
1210	1670lm/17W	2640lm/27W
1500	2080lm/20W	3300lm/33W
1800	2500lm/24W	3960lm/39W

Lumen Values: Luminarie luminous flux at 4000K/CRI>80. Other configurations on request.



W Snow White



S Radiant Silver



U Urban Graphite



B Jet Black



H Anodic Champagne



K Satin Copper