

## Beam Me Up-A4

Surface mounted luminaire - Wallwasher

Article code: MA4OWL-830M-D1200-G



Illustrations may only be similar and serve as an orientation.




Beam Me Up-A4. LED. Design surface mounted luminaire for ceiling mounting with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Snow White. Direct only light distribution with wide asymmetrical beam angle (Wallwasher). Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Reflector: Satin Gold. Dimmable DALI. DxH

(round). D=1200mm. H=580/269mm. Medium-power current. 8696lm. 104W. 20kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

## Beam Me Up-A4

Surface mounted luminaire - Wallwasher

Article code: MA4OWL-830M-D1200-G



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Beam Me Up-A4
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Snow White
Light characteristics	Wallwasher
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Reflector Colour Inside	Reflector: Satin Gold
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=1200mm
Height H (mm)	H=580/269mm
Current/Power	Medium-Power
Luminous Flux	8696lm
Power consumption	104W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	20kg

