lightnet

Beam Me Up-X1

Surface mounted luminaire - Direct/indirect light distribution Article code: MX1AWL-830M-D1200-W



Illustrations may only be similar and serve as an orientation.

Beam Me Up-X1. LED. Design surface mounted luminaire for ceiling mounting with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Snow White. Direct light distribution and indirect lighting corona. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=16. Reflector: Snow White. Dimmable DALI. DxH (round). D=1200mm. H=350+60mm. Medium-power current. 18204lm. 177W. 22,5kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 14.03.2024

lightnet


Beam Me Up-X1

Surface mounted luminaire - Direct/indirect light distribution

Article code: MX1AWL-830M-D1200-W

Customer / Project:

Note:





Productname	Beam Me Up-X1
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Snow White
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Reflector Colour Inside	Reflector: Snow White
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=1200mm
Height H (mm)	H=350+60mm
Current/Power	Medium-Power
Luminous Flux	18204lm
Power consumption	177W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
UGR	UGR<=16
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	22,5kg

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 14.03.2024