lightnet

Basic-X7

Surface mounted luminaire - Direct/indirect light distribution Article code: BX7AWE-830M-D500



Illustrations may only be similar and serve as an orientation.

Basic-X7. LED. Wall or ceiling mounted luminaire. Luminaire body with distance-spacer. Luminaire body made of high-quality aluminum profile. Surface finish Snow White. Direct light distribution and indirect lighting corona. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Switchable. DxH (round). D=500mm. H=18+24mm. Medium-power current. 2805lm. 23W. 5,1kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 09.03.2024

lightnet


Basic-X7


Surface mounted luminaire - Direct/indirect light distribution

Article code: BX7AWE-830M-D500

Customer / Project:

Note:





Productname	Basic-X7
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Snow White
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Switchable
Length L/Diameter D (mm)	D=500mm
Height H (mm)	H=18+24mm
Current/Power	Medium-Power
Luminous Flux	2805lm
Power consumption	23W
Degree of protection	IP40
Certification	Prüfzeichen: ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	5,1kg

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 09.03.2024