
lightnet

Basic-Z3

Surface mounted luminaire - Direct light distribution







Article code: BZ3AWE-830M-D300-W

Basic-Z3. LED. Wall or ceiling mounted luminaire. Luminaire can be rotated and tilted via high-quality joint system, 345° rotation and 90° tilt. Luminaire body made of aluminium profile. 20mm setback lens optic set in a decorative ring. Surface finish Snow White. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Reflector: Snow White.


Switchable. DxH (round). D=300mm. H=58mm. Medium-power current. 776lm. 8W. 3,2kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

lightnet

Basic-Z3

Surface mounted luminaire - Direct light distribution







Article code: BZ3AWE-830M-D300-W

Customer / Project:		
Note:		

Productname Basic-Z3 Lamp LED

Installation Type Surface mounted luminaire

Surface finish Snow White

Colour temperature 3000K Colour Rendering Index (CRI) CRI>80

Optical system Microprismatic screen
Reflector Colour Inside Reflector: Snow White

Control Switchable
Length L/Diameter D (mm) D=300mm
Height H (mm) H=58mm

Current/Power Medium-Power Luminous Flux 776lm

Power consumption 8W

Power consumption 8W
Degree of protection IP40

LED lifetime L85B10 (tq 25°C) = 50.000h

UGR UGR<=19
Photometric code 8 30 / 3 3 9
Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 3,2kg



















