

## Basic-C3

Surface mounted luminaire with adapter for 3-phase tracks - Article code: BC3OWL-830H-D300-EB  
Direct light distribution



Illustrations may only be similar and serve as an orientation.


Basic-C3. LED. Surface mounted luminaire with adapter for 3-phase tracks. Luminaire can be rotated and tilted via high-quality joint system, 345° rotation and 90° tilt. Luminaire body made of aluminium profile with overall height of 58mm. 20mm setback lens optic set in a decorative ring. Surface finish Snow White. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform

illumination. Reflector: Jet Black. 3-phase track adaptor Eutrac. Dimmable DALI. DxH (round). D=300mm. H=58mm. High-power current. 1309lm. 13W. 3kg. Binning initial ≤ MacAdam 3. IP40. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

## Basic-C3

Surface mounted luminaire with adapter for 3-phase tracks - Direct light distribution

Article code: BC3OWL-830H-D300-EB



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Basic-C3
Lamp	LED
Installation Type	Surface mounted luminaire with adapter for 3-phase tracks
Surface finish	Snow White
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Reflector Colour Inside	Reflector: Jet Black
Adaptor	Eutrac Adaptor
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=300mm
Height H (mm)	H=58mm
Current/Power	High-Power
Luminous Flux	1309lm
Power consumption	13W
Degree of protection	IP40
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	3kg

