

## Basic-W5

Wall mounted luminaire - Direct/indirect light distribution

Article code: BW5OSL-830H-D300



Illustrations may only be similar and serve as an orientation.



Basic-W5. LED. Wall mounted luminaire. Luminaire body with 38mm visible overall height and minimalist edge of only 5mm. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Dimmable DALI. DxH (round). D=300mm. H=38mm. High-power current.

1945lm. 18W. 3kg. Binning initial  $\leq$  MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

## Basic-W5

Wall mounted luminaire - Direct/indirect light distribution

Article code: BW5OSL-830H-D300



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Basic-W5
Lamp	LED
Installation Type	Wall mounted luminaire
Surface finish	Radiant Silver
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=300mm
Height H (mm)	H=38mm
Current/Power	High-Power
Luminous Flux	1945lm
Power consumption	18W
Degree of protection	IP20
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	3kg

