

Lucille-W1

Wall mounted luminaire - Direct light distribution

Article code: UW1ABS-840M-D150-W



Illustrations may only be similar and serve as an orientation.




Lucille-W1. LED. Design luminaire with pantograph for wall mounting. Surface finish Jet Black. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. Power Supply through the wall. Switch&dim. DxWxH (luminaire head, round/Stand). D=150mm. W=383mm. H=

560mm. Medium-power current. 1000lm. 13W. 2,5kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Lucille-W1

Wall mounted luminaire - Direct light distribution

Article code: UW1ABS-840M-D150-W



Customer / Project: _____

Note: _____

Productname	Lucille-W1
Lamp	LED
Installation Type	Wall mounted luminaire
Surface finish	Jet Black
Light characteristics	Direct light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Adaptor	Power Supply wall
Control	Switch&dim
Length L/Diameter D (mm)	D=150mm
Width W (mm)	W=383mm
Height H (mm)	H=560mm
Current/Power	Medium-Power
Luminous Flux	1000lm
Power consumption	13W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	2,5kg

