lightnet

Beam Me Up-S1

Free standing luminaire - Direct/indirect light distribution

Article code: MS1AWX-827M-D450-CG-A



Illustrations may only be similar and serve as an orientation.

Beam Me Up-S1. LED. Design floor lamp, with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Snow White. Direct/indirect light distribution. Colour temperature: 2700K (Soft White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Reflector: Satin Gold. Dimmable. DxWxH (luminaire head, round/Stand). D= 450mm. H=2000/90mm. Medium-power current. 8462lm. 74W. 17,1kg. Binning initial <= MacAdam 3. Square base with soft corners. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25° C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 03.03.2024

lightnet

Beam Me Up-S1

Free standing luminaire - Direct/indirect light distribution


Article code: MS1AWX-827M-D450-CG-A



Customer / Project:

Note:

Productname	Beam Me Up-S1
Lamp	LED
Installation Type	Free standing luminaire
Surface finish	Snow White
Light characteristics	Direct/indirect light distribution
Colour temperature	2700K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Reflector Colour Inside	Reflector: Satin Gold
Control	Separately dimmable
Length L/Diameter D (mm)	D=450mm
Height H (mm)	H=2000/90mm
Current/Power	Medium-Power
Luminous Flux	8462lm
Power consumption	74W
Base-Type	Square base with soft corners
Plug	Schuko CEE 7/7 (E+F)
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 27 / 3 3 9
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	17,1kg



© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 03.03.2024