lightnet

Beam Me Up-S4

Free standing luminaire - Direct/indirect light distribution



Illustrations may only be similar and serve as an orientation.

1/2

Beam Me Up-S4. LED. Design floor lamp, with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Snow White. Direct/indirect light distribution. Colour temperature: 2700K (Soft White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Reflector: Jet Black. Dimmable. DxWxH (luminaire head, round/Stand). D= 650mm. H=2000/90mm. Medium-power

current. 11127lm. 93W. 27,5kg. Binning initial <= MacAdam 3. Square base with soft corners. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25° C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.


Article code: MS4AWX-827M-D650-CB-A


lightnet

Beam Me Up-S4

Free standing luminaire - Direct/indirect light distribution







Article code: MS4AWX-827M-D650-CB-A

Customer / Project:					
Note:					

Productname Beam Me Up-S4

Lamp LED

Installation Type Free standing luminaire

Surface finish Snow White

Light characteristics Direct/indirect light distribution

Separately dimmable

Colour temperature 2700K Colour Rendering Index (CRI) CRI>80

Optical system Microprismatic screen
Reflector Colour Inside Reflector: Jet Black

Control

Langeth I (Diamostar D (mana)

Length L/Diameter D (mm) D=650mm
Height H (mm) H=2000/90mm
Current/Power Medium-Power
Luminous Flux 11127lm
Power consumption 93W

Base-Type Square base with soft corners

Plug Schuko CEE 7/7 (E+F)

Degree of protection

LED lifetime L85B10 (tq 25°C) = 50.000h

UGR UGR<=19
Photometric code 8 27 / 3 3 9

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 27,5kg

