lightnet

Beam Me Up-S4

Free standing luminaire - Direct/indirect light distribution



Illustrations may only be similar and serve as an orientation.

Beam Me Up-S4. LED. Design floor lamp, with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Jet Black. Direct/indirect light distribution. Colour temperature: 2700K (Soft White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Reflector: Satin Gold. Dimmable. DxWxH (luminaire head, round/Stand). D= 650mm. H=2000/90mm. Medium-power

current. 11127lm. 93W. 27,5kg. Binning initial <= MacAdam 3. Square base with soft corners. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25° C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.


Article code: MS4ABX-827M-D650-CG-A


lightnet

Beam Me Up-S4

Free standing luminaire - Direct/indirect light distribution







Article code: MS4ABX-827M-D650-CG-A

Customer	/ Project:			
Note:				

Productname Beam Me Up-S4

Lamp LED

Installation Type Free standing luminaire

Surface finish Jet Black

Reflector: Satin Gold

Separately dimmable

Colour temperature 2700K Colour Rendering Index (CRI) CRI>80

Optical system Microprismatic screen

Reflector Colour Inside

Control

 $\begin{array}{lll} \mbox{Length L/Diameter D (mm)} & \mbox{D=650mm} \\ \mbox{Height H (mm)} & \mbox{H=2000/90mm} \\ \mbox{Current/Power} & \mbox{Medium-Power} \end{array}$

Luminous Flux
Power consumption

Base-Type Square base with soft corners

11127lm

Plug Schuko CEE 7/7 (E+F)

Degree of protection IP

LED lifetime L85B10 (tq 25°C) = 50.000h

UGR UGR<=19
Photometric code 8 27 / 3 3 9

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 27,5kg

