

Midpin-W2

Spotlight for wall surface mounting - Direct/indirect light distribution

Article code: DW2BWE-940M-G



Illustrations may only be similar and serve as an orientation.

Midpin-W2. LED. Spotlight for wall surface mounting. Luminaire body made of high-quality aluminum profile. Medium 30°. Surface finish Snow White. Direct/indirect light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >90. Reflector: Satin Gold. Switchable. DxHxW (spots). D=40mm. W=50mm. H=600mm. Medium-power current. 1500lm. 22W. 0,5kg. Binning initial

<= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG1 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Midpin-W2

Spotlight for wall surface mounting -
Direct/indirect light distribution



Article code: DW2BWE-940M-G

Customer / Project: _____

Note: _____

Productname	Midpin-W2
Lamp	LED
Installation Type	Spotlight for wall surface mounting
Lens Angle	Medium 30°
Surface finish	Snow White
Light characteristics	Direct/indirect light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>90
Reflector Colour Inside	Reflector: Satin Gold
Control	Switchable
Length L/Diameter D (mm)	D=40mm
Width W (mm)	W=50mm
Height H (mm)	H=600mm
Current/Power	Medium-Power
Luminous Flux	1500lm
Power consumption	22W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	9 40 / 3 3 9
Photobiological class	RG1 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	0,5kg

