

## Midpin-W2

Spotlight for wall surface mounting - Direct/indirect light distribution

Article code: DW2CAL-927M-S



Illustrations may only be similar and serve as an orientation.

Midpin-W2. LED. Spotlight for wall surface mounting. Luminaire body made of high-quality aluminum profile. Flood 40°. Surface finish Satin Silver. Direct/indirect light distribution. Colour temperature: 2700K (Soft White). Colour Rendering Index (CRI): >90. Reflector: Radiant Silver. Dimmable DALI. DxHxW (spots). D=40mm. W=50mm. H=600mm. Medium-power current. 1240lm. 22W. 0,5kg.

Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG1 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Midpin-W2

Spotlight for wall surface mounting -  
Direct/indirect light distribution



Article code: DW2CAL-927M-S

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Midpin-W2
Lamp	LED
Installation Type	Spotlight for wall surface mounting
Lens Angle	Flood 40°
Surface finish	Satin Silver
Light characteristics	Direct/indirect light distribution
Colour temperature	2700K
Colour Rendering Index (CRI)	CRI>90
Reflector Colour Inside	Reflector: Radiant Silver
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=40mm
Width W (mm)	W=50mm
Height H (mm)	H=600mm
Current/Power	Medium-Power
Luminous Flux	1240lm
Power consumption	22W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	9 27 / 3 3 9
Photobiological class	RG1 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	0,5kg

IP20

LV

IK 02

RG1

≤3 MacAdam

MEDIUM POWER L85B10 50.000h

CE

UK CA