lightnet

Liquid Line-CX

Surface mounted luminaire with adapter for 3-phase tracks - Direct light distribution

Article code: QCXOSE-830M-L2055-G



Illustrations may only be similar and serve as an orientation.

Liquid Line-CX. LED. Surface mounted luminaire with adapter for 3-phase tracks. Luminaire body with fine radii made of aluminium, manufactured from a single casting without visible seams. Surface finish Radiant Silver. Direct only lightdistribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. 3-phase track adaptor Global. Switchable. LxWxH (rectangular). L=2055mm.

W=40mm. H=65mm. Medium-power current. 2983lm. 27W. 4,3kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 03.03.2024

lightnet

Liquid Line-CX


Surface mounted luminaire with adapter for 3-phase tracks - Direct light distribution

Article code: QCXOSE-830M-L2055-G



Customer / Project:

Note:





Productname	Liquid Line-CX
Lamp	LED
Installation Type	Surface mounted luminaire with adapter for 3-phase tracks
Surface finish	Radiant Silver
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Adaptor	Global Adaptor
Control	Switchable
Length L/Diameter D (mm)	L=2055mm
Width W (mm)	W=40mm
Height H (mm)	H=65mm
Current/Power	Medium-Power
Luminous Flux	2983lm
Power consumption	27W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	4,3kg

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 03.03.2024