

## Liquid Line-CX

Surface mounted luminaire with adapter for 3-phase tracks - Article code: QCXOBE-840M-L2055-G  
Direct light distribution




Illustrations may only be similar and serve as an orientation.

Liquid Line-CX. LED. Surface mounted luminaire with adapter for 3-phase tracks. Luminaire body with fine radii made of aluminium, manufactured from a single casting without visible seams. Surface finish Jet Black. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. 3-phase track adaptor Global. Switchable. LxWxH (rectangular). L=2055mm.

W=40mm. H=65mm. Medium-power current. 3190lm. 27W. 4,3kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

## Liquid Line-CX

Surface mounted luminaire with adapter for 3-phase tracks - Direct light distribution



Article code: QCXOBE-840M-L2055-G

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Liquid Line-CX
Lamp	LED
Installation Type	Surface mounted luminaire with adapter for 3-phase tracks
Surface finish	Jet Black
Light characteristics	Direct light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Adaptor	Global Adaptor
Control	Switchable
Length L/Diameter D (mm)	L=2055mm
Width W (mm)	W=40mm
Height H (mm)	H=65mm
Current/Power	Medium-Power
Luminous Flux	3190lm
Power consumption	27W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	4,3kg

