

Liquid Line-C5

Spotlight with adapter for 3-phase tracks - Direct light distribution

Article code: QC5OWE-840M-L139-G



Illustrations may only be similar and serve as an orientation.



Liquid Line-C5. LED. Spotlight with adapter for 3-phase tracks. 345° rotatable and 90° swivelable. Luminaire body with fine radii made of aluminium, manufactured from a single casting without visible seams. Surface finish Snow White. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. 3-phase track adaptor Global. Switchable. LxWxH (rectangular). L=139mm. W=40mm.

H=105mm. Medium-power current. 530lm. 7W. 0,9kg. Binning initial ≤ MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Liquid Line-C5

Spotlight with adapter for 3-phase tracks - Direct light distribution

Article code: QC5OWE-840M-L139-G



Customer / Project: _____

Note: _____

| | |
|------------------------------|---|
| Productname | Liquid Line-C5 |
| Lamp | LED |
| Installation Type | Spotlight with adapter for 3-phase tracks |
| Surface finish | Snow White |
| Light characteristics | Direct light distribution |
| Colour temperature | 4000K |
| Colour Rendering Index (CRI) | CRI>80 |
| Optical system | Opal diffuser |
| Adaptor | Global Adaptor |
| Control | Switchable |
| Length L/Diameter D (mm) | L=139mm |
| Width W (mm) | W=40mm |
| Height H (mm) | H=105mm |
| Current/Power | Medium-Power |
| Luminous Flux | 530lm |
| Power consumption | 7W |
| Degree of protection | IP20 |
| LED lifetime | L85B10 (tq 25°C) = 50.000h |
| Photometric code | 8 40 / 3 3 9 |
| Photobiological class | RG0 (EN62471) |
| Indoor/Outdoor | Indoor: ta [ambient] max. 25°C |
| Weight (kg) | 0,9kg |

