

Basic-Y9

Surface mounted luminaire - Direct only omnidirectional light distribution

Article code: BY9AUL-830M-D300



Illustrations may only be similar and serve as an orientation.

Basic-Y9. LED. Wall or ceiling mounted luminaire. Luminaire body made of cast acrylic glass. Surface finish: Urban Graphite. Direct only omnidirectional light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<= 19. Dimmable DALI. DxH (round). D=300mm. H=55+22mm. Medium-power

current. 589lm. 5W. 3,5kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.


Basic-Y9

Surface mounted luminaire - Direct only
omnidirectional light distribution

Article code: BY9AUL-830M-D300

Customer / Project: _____

Note: _____



Productname	Basic-Y9
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Urban Graphite
Light characteristics	Direct only omnidirectional light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=300mm
Height H (mm)	H=55+22mm
Current/Power	Medium-Power
Luminous Flux	589lm
Power consumption	5W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	3,5kg

