

## Basic-G9

Pendant luminaire - Direct only omnidirectional light distribution

Article code: BG9OUL-827M-D400-U



Illustrations may only be similar and serve as an orientation.

Basic-G9. LED. Pendant luminaire. Luminaire body made of cast acrylic glass. Surface finish: Urban Graphite. Direct only omnidirectional light distribution. Colour temperature: 2700K (Soft White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Dimmable DALI. DxH (round). D= 400mm. H=55+22mm. Central cord suspension with ceiling rose and power supply cable (Set). Pendant length max 1500mm. Power supply:

transparent. Ceiling rose: Matching luminaire`s surface colour. Medium-power current. 1618lm. 13W. 4,4kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

## Basic-G9

Pendant luminaire - Direct only omnidirectional light distribution

Article code: BG9OUL-827M-D400-U



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_



Productname	Basic-G9
Lamp	LED
Installation Type	Pendant luminaire
Surface finish	Urban Graphite
Light characteristics	Direct only omnidirectional light distribution
Colour temperature	2700K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=400mm
Height H (mm)	H=55+22mm
Current/Power	Medium-Power
Luminous Flux	1618lm
Power consumption	13W
Suspension	Central susp. (Set)
Ceiling rose colour	Ceiling rose: Matching luminaire`s surface colour
Pendant length (mm)	Pendant length max 1500mm
Degree of protection	IP20
Cable Colour	Power supply: transparent
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 27 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	4,4kg

