## lightnet

## Basic-N3

Recessed mounted luminaire (trimless) for ceilings with shadow gap, mounting brackets incl - Direct/indirect light

Article code: BN3OWL-827M-D400-WW



Illustrations may only be similar and serve as an orientation.

Basic-N3. LED. Recessed mounted luminaire with shadow gap for frameless mounting in plasterboard ceilings. Mounting brackets included. Luminaire body made of high-quality aluminum profile. Surface finish Snow White. Direct light distribution and indirect lighting corona. Colour temperature: 2700K (Soft White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Reflector: Snow White. Aura colour white. Dimmable DALI. DxH


(round). D=400mm. H=78mm. Medium-power current. 1711lm. 24W. 5,7kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.


## lightnet

## Basic-N3

Recessed mounted luminaire (trimless) for ceilings with shadow gap, mounting brackets







Article code: BN3OWL-827M-D400-WW

Customer / Project:					
Note:					

Productname Basic-N3 Lamp LED

Installation Type Recessed mounted luminaire (trimless)

for ceilings with shadow gap, mounting

brackets incl

Surface finish Snow White

Light characteristics Direct/indirect light distribution

Colour temperature 2700K

Colour Rendering Index (CRI) CRI>80

Optical system Opal diffuser

Reflector Colour Inside Reflector: Snow White

Aura colour
Control
Length L/Diameter D (mm)
Height H (mm)
Current/Power
Luminous Flux

Aura white
Dimmable (DALI)
D=400mm
H=78mm
Medium-Power

Power consumption 24W
Degree of protection IP40

LED lifetime L85B10 (tq  $25^{\circ}$ C) = 50.000h

Photometric code 8 27 / 3 3 9 Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 5,7kg

