lightnet

Basic-L3

Recessed luminaire for ceilings, mounting brackets incl - Article code: BL3ASL-840E-D330-S Direct light distribution



Illustrations may only be similar and serve as an orientation.

Basic-L3. LED. Recessed luminaire for mounting in sawn ceiling openings, mounting brackets incl. Luminaire body with increased stability for installation. Surface finish RadiaSilver. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Reflector: Radiant Silver. Dimmable DALI. DxH (round). D=330mm. H= 100mm.


Low-power current. 880lm. 7W. 3,1kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

lightnet

Basic-L3

Recessed luminaire for ceilings, mounting brackets incl - Direct light distribution







Article code: BL3ASL-840E-D330-S

Customer / Project:					
Note:					

Productname Basic-L3 Lamp LED

Installation Type Recessed luminaire for ceilings,

mounting brackets incl

Surface finish Radiant Silver

Colour temperature 4000K Colour Rendering Index (CRI) CRI>80

Optical system Microprismatic screen
Reflector Colour Inside Reflector: Radiant Silver
Control Dimmable (DALI)

Length L/Diameter D (mm) D=330mm
Height H (mm) H=100mm
Current/Power Low-Power
Luminous Flux 880Im
Power consumption 7W
Degree of protection IP20

LED lifetime L90B10 (tq 25° C) = 50.000h

UGR UGR<=19
Photometric code 8 40 / 3 3 9
Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 3,1kg

