lightnet

Basic-L3

Recessed luminaire for ceilings, mounting brackets incl - Direct light distribution

Article code: BL3ABL-840E-D330-B



Illustrations may only be similar and serve as an orientation.

Basic-L3. LED. Recessed luminaire for mounting in sawn ceiling openings, mounting brackets incl. Luminaire body with increased stability for installation. Surface finish Jet Black. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Reflector: Jet Black. Dimmable DALI. DxH (round). D=330mm. H=100mm. Low-power current. 880lm. 7W. 3,1kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.


Date: 31.01.2024

lightnet

Basic-L3


Recessed luminaire for ceilings, mounting brackets incl - Direct light distribution


Article code: BL3ABL-840E-D330-B



Customer / Project:

Note:





Productname	Basic-L3
Lamp	LED
Installation Type	Recessed luminaire for ceilings, mounting brackets incl
Surface finish	Jet Black
Light characteristics	Direct light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Reflector Colour Inside	Reflector: Jet Black
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=330mm
Height H (mm)	H=100mm
Current/Power	Low-Power
Luminous Flux	880lm
Power consumption	7W
Degree of protection	IP20
LED lifetime	L90B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	3,1kg

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 31.01.2024