

lightnet

Beam Me Up-T2

Table light - Direct/indirect light distribution

Article code: MT2AWX-830M-D450-GW-A



Illustrations may only be similar and serve as an orientation.

Beam Me Up-T2. LED. Design table lamp, with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Snow White. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Reflector: Snow White. Dimmable. DxH (luminaire head, round/Stand). D=450mm. H=90/600mm.

Medium-power current. 3310lm. 33W. 9,7kg. Binning initial <= MacAdam 3. Table base matching luminaire`s outer surface colour. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

lightnet

Beam Me Up-T2

Table light - Direct/indirect light distribution

Article code: MT2AWX-830M-D450-GW-A

Customer / Project: _____

Note: _____

| | |
|------------------------------|------------------------------------|
| Productname | Beam Me Up-T2 |
| Lamp | LED |
| Installation Type | Table light |
| Surface finish | Snow White |
| Light characteristics | Direct/indirect light distribution |
| Colour temperature | 3000K |
| Colour Rendering Index (CRI) | CRI>80 |
| Optical system | Microprismatic screen |
| Reflector Colour Inside | Reflector: Snow White |
| Control | Separately dimmable |
| Length L/Diameter D (mm) | D=450mm |
| Height H (mm) | H=90/600mm |
| Current/Power | Medium-Power |
| Luminous Flux | 3310lm |
| Power consumption | 33W |
| Base-Type | Table base |
| Plug | Schuko CEE 7/7 (E+F) |
| Degree of protection | IP20 |
| LED lifetime | L85B10 (tq 25°C) = 50.000h |
| UGR | UGR<=19 |
| Photometric code | 8 30 / 3 3 9 |
| Photobiological class | RG0 (EN62471) |
| Indoor/Outdoor | Indoor: ta [ambient] max. 25°C |
| Weight (kg) | 9,7kg |

