

lightnet

Beam Me Up-T2

Table light - Direct/indirect light distribution

Article code: MT2ABX-830M-D450-GG-A



Illustrations may only be similar and serve as an orientation.

Beam Me Up-T2. LED. Design table lamp, with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Jet Black. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Reflector: Satin Gold. Dimmable. DxH (luminaire head, round/Stand). D=450mm. H=90/600mm.

Medium-power current. 3310lm. 33W. 9,7kg. Binning initial <= MacAdam 3. Table base matching luminaire`s outer surface colour. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

lightnet

Beam Me Up-T2

Table light - Direct/indirect light distribution

Article code: MT2ABX-830M-D450-GG-A

Customer / Project: _____

Note: _____

Productname	Beam Me Up-T2
Lamp	LED
Installation Type	Table light
Surface finish	Jet Black
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Reflector Colour Inside	Reflector: Satin Gold
Control	Separately dimmable
Length L/Diameter D (mm)	D=450mm
Height H (mm)	H=90/600mm
Current/Power	Medium-Power
Luminous Flux	3310lm
Power consumption	33W
Base-Type	Table base
Plug	Schuko CEE 7/7 (E+F)
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	9,7kg

