

## Midpin-M2

Recessed mounted spotlight - Direct light distribution

Article code: DM2BBL-930M-B



Illustrations may only be similar and serve as an orientation.

Midpin-M2. LED. Recessed mounted spotlight with surrounding frame for installation in ceilings with cut-out openings. Medium 30°. Surface finish Jet Black. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >90. Reflector: Jet Black. Dimmable DALI. DxH (spots). D=40mm. H=73mm. Medium-power current. 710lm. 11W. 0,8kg. Binning initial <=

MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG1 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

## Midpin-M2

Recessed mounted spotlight - Direct light distribution



Article code: DM2BBL-930M-B

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Midpin-M2
Lamp	LED
Installation Type	Recessed mounted spotlight
Lens Angle	Medium 30°
Surface finish	Jet Black
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>90
Reflector Colour Inside	Reflector: Jet Black
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=40mm
Height H (mm)	H=73mm
Current/Power	Medium-Power
Luminous Flux	710lm
Power consumption	11W
Degree of protection	IP20
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	9 30 / 3 3 9
Photobiological class	RG1 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	0,8kg

