

lightnet

# Liquid Line-FX

Recessed mounted light system, mounting brackets incl - Direct light distribution

Article code:
QFXLWE-830E-STRUCTURE-Lxxxx-W





Illustrations may only be similar and serve as an orientation.

Liquid Line-FX. LED. Recessed mounted light system, mounting brackets incl. Luminaire body made of high-quality aluminum profile. Surface finish Snow White. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Lens Louvre: precision lenses with louvre. High glare limitation, compatible for office applications. UGR<=19. Reflector: Snow White. Switchable. according to drawing. LxWxH (flexible) . Special length L=xxxxmm. W=40mm. H= 65mm. Low-power current. 1580lm/m. 13W/m. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.



© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 10.03.2024

lightnet

# Liquid Line-FX


Recessed mounted light system, mounting brackets incl - Direct light distribution


Article code:
QFXLWE-830E-STRUCTURE-Lxxxx-W


Customer / Project:

Note:






| | |
|---|---|
| Productname | Liquid Line-FX |
| Lamp | LED |
| Installation Type | Recessed mounted light system, mounting brackets incl |
| Surface finish | Snow White |
| Light characteristics | Direct light distribution |
| Colour temperature | 3000K |
| Colour Rendering Index (CRI) | CRI>80 |
| Optical system | Lens Louvre |
| Reflector Colour Inside | Reflector: Snow White |
| Control | Switchable |
| Length L/Diameter D (mm) | Special length L=xxxxmm |
| Width W (mm) | W=40mm |
| Height H (mm) | H=65mm |
| Current/Power | Low-Power |
| Luminous Flux | 1580lm/m |
| Power consumption | 13W/m |
| Degree of protection | IP20 |
| LED lifetime | L90B10 (tq 25°C) = 50.000h |
| UGR | UGR<=19 |
| Photometric code | 8 30 / 3 3 9 |
| Photobiological class | RG0 (EN62471) |
| Indoor/Outdoor | Indoor: ta [ambient] max. 25°C |
| Other | according to drawing |



© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 10.03.2024