

## Cubic-F7

Free standing luminaire - Direct/indirect light distribution

Article code: CF7ABR-830H-L1320-H-A



Illustrations may only be similar and serve as an orientation.



Cubic-F7. LED. Free standing luminaire. Two luminaire heads with 25mm minimalist overall height. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for reduced luminance in office areas. UGR<=19. Swarm Control. LxWxH (luminaire head, rectangular/Stand). L=1320mm. W=300mm. H=2000/25mm. High-power current. 28611lm.

184W. 24,3kg. Binning initial <= MacAdam 3. H-formed floor base matching luminaire`s outer surface colour. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

## Cubic-F7

Free standing luminaire - Direct/indirect light distribution

Article code: CF7ABR-830H-L1320-H-A



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Cubic-F7
Lamp	LED
Installation Type	Free standing luminaire
Surface finish	Jet Black
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Swarm Control
Length L/Diameter D (mm)	L=1320mm
Width W (mm)	W=300mm
Height H (mm)	H=2000/25mm
Current/Power	High-Power
Luminous Flux	2861lm
Power consumption	184W
Base-Type	H-base
Plug	Schuko CEE 7/7 (E+F)
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L80B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 30 / 3 3 9
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	24,3kg

