
lightnet

Cubic-F2

Free standing luminaire - Direct/indirect light distribution

Article code: CF2AER-830H-L600-U-A





Illustrations may only be similar and serve as an orientation.

Cubic-F2. LED. Free standing luminaire. Luminaire head with 25mm minimalist overall height. Luminaire body made of high-quality aluminum profile. Surface finish Silver Anodised. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for reduced luminance in office areas. UGR<=19. Swarm Control. LxWxH (luminaire head, rectangular/Stand). L=600mm. W=300mm. H= 2000/25mm. High-power current. 14306lm. 92W. 19,5kg. Binning initial <= MacAdam 3. U-formed floor base matching luminaire`s outer surface colour. Plug Schuko CEE 7/7 (Type E+F). IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 02.03.2024

lightnet

Cubic-F2


Free standing luminaire - Direct/indirect light distribution


Article code: CF2AER-830H-L600-U-A



Customer / Project:

Note:





Productname	Cubic-F2
Lamp	LED
Installation Type	Free standing luminaire
Surface finish	Silver Anodised
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Swarm Control
Length L/Diameter D (mm)	L=600mm
Width W (mm)	W=300mm
Height H (mm)	H=2000/25mm
Current/Power	High-Power
Luminous Flux	14306lm
Power consumption	92W
Base-Type	U-base
Plug	Schuko CEE 7/7 (E+F)
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L80B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 30 / 3 3 9
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	19,5kg

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 02.03.2024