
lightnet

Liquid Line-F3

Recessed mounted light system, mounting brackets incl - Direct light distribution

Article code:
QF3ABE-830H-STRUCTURE-Lxxxx





Illustrations may only be similar and serve as an orientation.

Liquid Line-F3. LED. Recessed mounted light system, mounting brackets incl. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for reduced luminance in office areas. Switchable. according to drawing. LxWxH (flexible) . Special length L=xxxxmm. W= 60mm. H=74mm. High-power current. 2141lm/m. 31W/m. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 10.03.2024

lightnet

Liquid Line-F3


Recessed mounted light system, mounting brackets incl - Direct light distribution


Article code:
QF3ABE-830H-STRUCTURE-Lxxxx

Customer / Project:

Note:







Productname	Liquid Line-F3
Lamp	LED
Installation Type	Recessed mounted light system, mounting brackets incl
Surface finish	Jet Black
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Switchable
Length L/Diameter D (mm)	Special length L=xxxxmm
Width W (mm)	W=60mm
Height H (mm)	H=74mm
Current/Power	High-Power
Luminous Flux	2141lm/m
Power consumption	31W/m
Degree of protection	IP20
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Other	according to drawing

© Lightnet GmbH, Zollstockgürtel 65, D-50969 Köln, Tel. +49 (0) 221 22 25 26-0, info@lightnet.de, www.lightnet.de
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 10.03.2024