

Beam Me Up-X3

Surface mounted luminaire - Direct/indirect light distribution Article code: MX3OBL-830H-D650-B



Illustrations may only be similar and serve as an orientation.


Beam Me Up-X3. LED. Design surface mounted luminaire for ceiling mounting with a setback lens optic in a decorative ring. Luminaire head made of high-quality processed fiberglass. Surface finish Jet Black. Direct light distribution and indirect lighting corona. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and uniform illumination. Reflector: Jet

Black. Dimmable DALI. DxH (round). D=650mm. H=90+30mm. High-power current. 7377lm. 63W. 7,5kg. Binning initial ≤ MacAdam 3. IP40. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Beam Me Up-X3

Surface mounted luminaire - Direct/indirect light distribution

Article code: MX3OBL-830H-D650-B



Customer / Project: _____

Note: _____

Productname	Beam Me Up-X3
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Jet Black
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Reflector Colour Inside	Reflector: Jet Black
Control	Dimmable (DALI)
Length L/Diameter D (mm)	D=650mm
Height H (mm)	H=90+30mm
Current/Power	High-Power
Luminous Flux	7377lm
Power consumption	63W
Degree of protection	IP40
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	7,5kg

IP40

~220-240V

50-60 Hz

IK 02

RG0

≤3 MACADAM

MEDIUM POWER L85B10 50000h

HIGH POWER L80B10 50000h

CE

UK CA