

Ringo Star-A3

Surface mounted luminaire - Direct light distribution

Article code: RA3ASE-827E-D1500



Illustrations may only be similar and serve as an orientation.




Ringo Star-A3. LED. Surface mounted luminaire for walls or ceilings. Luminaire body made of aluminium profile with 60mm track width. Surface finish Radiant Silver. Direct only light distribution. Colour temperature: 2700K (Soft White). Colour Rendering Index (CRI): >80. Microprismatic screen for reduced luminance in office areas. Switchable. DxHxW (round). D=1500mm. W=60mm. H=85mm. Low-power

current. 5255lm. 69W. 14kg. Binning initial \leq MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25° C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Ringo Star-A3

Surface mounted luminaire - Direct light distribution

Article code: RA3ASE-827E-D1500



Customer / Project: _____

Note: _____

Productname	Ringo Star-A3
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Radiant Silver
Light characteristics	Direct light distribution
Colour temperature	2700K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Switchable
Length L/Diameter D (mm)	D=1500mm
Width W (mm)	W=60mm
Height H (mm)	H=85mm
Current/Power	Low-Power
Luminous Flux	5255lm
Power consumption	69W
Degree of protection	IP20
LED lifetime	L90B10 (tq 25°C) = 50.000h
Photometric code	8 27 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	14kg

