

## Caleo-P6

Pendant luminaire - Direct/indirect light distribution

Article code: AP6OSE-827H-Q600-PS



Illustrations may only be similar and serve as an orientation.


Caleo-P6. LED. Pendant luminaire in soft-edge design. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct/indirect light distribution. Colour temperature: 2700K (Soft White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and uniform illumination. Reflector: Radiant Silver. Switchable. LxWxH (square). L= 600mm. W=600mm. H=25mm. Rod suspension with ceiling rose (Set). Pendant length on request. Ceiling

rose: Matching luminaire`s surface colour. High-power current. 8686lm. 73W. 7,2kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

## Caleo-P6

Pendant luminaire - Direct/indirect light distribution

Article code: AP6OSE-827H-Q600-PS



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Caleo-P6
Lamp	LED
Installation Type	Pendant luminaire
Surface finish	Radiant Silver
Light characteristics	Direct/indirect light distribution
Colour temperature	2700K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Reflector Colour Inside	Reflector: Radiant Silver
Control	Switchable
Length L/Diameter D (mm)	L=600mm
Width W (mm)	W=600mm
Height H (mm)	H=25mm
Current/Power	High-Power
Luminous Flux	8686lm
Power consumption	73W
Suspension	Rod susp. (Set)
Ceiling rose colour	Ceiling rose: Matching luminaire`s surface colour
Pendant length (mm)	Pendant length on request
Degree of protection	IP20
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 27 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	7,2kg

