

Matric-A3

Surface mounted light-line - Direct light distribution

Article code: LA3LWL-830H-Lxxxx-W



Illustrations may only be similar and serve as an orientation.



Matric-A3. LED. Wall or ceiling mounted light-line. Luminaire body made of high-quality aluminum profile. Surface finish Snow White. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Lens Louvre: precision lenses with louvre. High glare limitation, compatible for office applications. Reflector Snow White. Dimmable DALI. according to drawing. LxWxH (rectangular). Special length L=xxxxmm. W=55mm. H=75mm.

High-power current. 3441lm/m. 26W/m. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.



Matric-A3

Surface mounted light-line - Direct light distribution

Article code: LA3LWL-830H-Lxxxx-W

Customer / Project: _____

Note: _____



Productname	Matric-A3
Lamp	LED
Installation Type	Surface mounted light-line
Surface finish	Snow White
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Lens Louvre
Reflector Colour Inside	Reflector: Snow White
Control	Dimmable (DALI)
Length L/Diameter D (mm)	Special length L=xxxxmm
Width W (mm)	W=55mm
Height H (mm)	H=75mm
Current/Power	High-Power
Luminous Flux	3441lm/m
Power consumption	26W/m
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Other	according to drawing

