


Matric-M3

Recessed mounted ceiling light line (trimless) - Direct light distribution

Article code: LM3GEE-830M-Lxxxx-B



Illustrations may only be similar and serve as an orientation.





Matric-M3. LED. Recessed mounted ceiling light line (trimless) suitable for mounting in plasterboard ceilings. Luminaire body made of high-quality aluminum profile. Surface finish Silver Anodised. Installation brackets (set) incl. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Wall-Washer for asymmetrical light distribution. Switchable. LxWxH (rectangular). according to drawing. Special length L=xxxxmm. W=55mm. H=75mm. Medium-

power current. 1187lm/m. 16W/m. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated.

Matric-M3

Recessed mounted ceiling light line (trimless) -
Direct light distribution

Article code: LM3GEE-830M-Lxxxx-B



Customer / Project: _____

Note: _____

Productname	Matric-M3
Lamp	LED
Installation Type	Recessed mounted ceiling light line (trimless)
Surface finish	Silver Anodised
Installation	Installation brackets (set) incl
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Wall-Washer
Control	Switchable
Length L/Diameter D (mm)	Special length L=xxxxmm
Width W (mm)	W=55mm
Height H (mm)	H=75mm
Current/Power	Medium-Power
Luminous Flux	1187lm/m
Power consumption	16W/m
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Other	according to drawing

