

Midpoint A6 | Surface



FR Projecteur LED pour montage en saillie/plafonnier. Orientable à 350° et pivotant à 90°. Driver/Convertisseur intégré dans le corps du luminaire, au choix allumage ON/OFF ou dimmable (DALI). Corps du luminaire en aluminium thermolaqué/poudré blanc, argent, noir ou champagne. Autres options de finition voir Lightnet-Surface-Collection ou RAL au choix. Module/COB LED XICATO ARTIST en option pour une qualité d'éclairage maximale et un rendu des couleurs exceptionnel (IRC>97) + 5 ans de garantie sur le niveau des couleurs (MacAdam≤3) ou ECO pour une efficacité énergétique et un rapport qualité-prix optimal + IRC supérieur à 90 inclus. Température de couleur 2700K, 3000K ou 4000K. Réflecteur avec optique de lentille interchangeable et facettes à réflexion sphérique. Angle d'ouverture/faisceau: 10° (Spot), 20° (Medium), 35° (Flood) ou 50° (Wide Flood). Adaptateur Rail-Track 3-Phases au choix EUTRAC ou GLOBAL. Diffuseur transparent de fermeture standard. Filtres divers supplémentaires et/ou filtre nid d'abeilles en option.

ES Reflector LED para montaje en superficie. Se puede girar 350° horizontal y girar 90° vertical. Balastro integrado en el luminaria, opcionalmente conmutable de forma simple o con regulación continua (DALI). La carcasa de aluminio con cardán pintado en blanco, plata, negro o champán. Acabados adicionales según Light-Surface Collection o RAL seleccionable. LED Engine opcionalmente XICATO ARTIST para una máxima calidad de iluminación con la mejor reproducción cromática (CRI>97) y una garantía de 5 años para la constancia del color (MacAdam≤3) o ECO para una máxima eficiencia energética con una óptima relación calidadprecio y CRI>90. Temperatura de color 2700K, 3000K o 4000K. Óptica de reflector de lentes intercambiables con óptica de facetas esféricas. Ángulo del rayo: 10° (Spot), 20° (Medium), 35° (Flood) o 50° (Wide Flood). Anillo reflector disponible en varios colores. Cubierta despejada estándar. Opcionalmente filtros adicionales o rejilla de panal.

PA6BSE-927FM-BK

Product Family	P: Midpoint
Type	A6: Direct only
Beam Angle	A: Spot 10°, B: Medium 20°, C: Flood 35°, D: Wide Flood 50°
Surface Finish	W: Snow White, V: Ivory White, S: Radiant Silver, B: Jet Black, H: Anodic Champagne
Control Gear	E: On/Off, L: DALI, H: Touch-Dim
Colour Rendering	9: CRI>90
Colour Temperature	27: 2700K, 30: 3000K, 40: 4000K
Led-Engine	F: Eco [Ra> 90], A: Artist [Ra> 97, Xicato]
Power	E: Low Power M: Medium Power
Optic Ring	W: Snow White, V: Ivory White, S: Radiant Silver, B: Jet Black, H: Anodic Champagne, G: Satin Gold, K: Satin Copper
Cover	K: Clear Cover [Standard], P: Prismatic Lens, H: Honeycomb Louvre
On Request	Optic Removal Tool for clear cover



Spot 10° Led Engine Eco, Medium Power

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	25250/12700	0.24 m
2 m	6312/3175	0.48 m
3 m	2806/1411	0.72 m
4 m	1578/794	0.95 m

LED Engine	2700K	3000K	4000K
Eco Low Power [19W]	1230 lm	1350 lm	1440 lm
Eco Medium Power [31W]	1660 lm	1860 lm	2020 lm
Artist Low Power [19W]	1040 lm	1090 lm	1190 lm
Artist Medium Power [31W]	1400 lm	1480 lm	1560 lm

Medium 20° Led Engine Eco, Medium Power

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	17447/8455	0.32 m
2 m	4362/2114	0.64 m
3 m	1939/939	0.96 m
4 m	1090/528	1.30 m

LED Engine	2700K	3000K	4000K
Eco Low Power [19W]	1580 lm	1740 lm	1850 lm
Eco Medium Power [31W]	2360 lm	2640 lm	2870 lm
Artist Low Power [19W]	1330 lm	1390 lm	1510 lm
Artist Medium Power [31W]	1980 lm	2110 lm	2220 lm

Flood 35° Led Engine Eco, Medium Power

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	6251/2731	0.63 m
2 m	1563/683	1.30 m
3 m	695/303	1.90 m
4 m	391/171	2.50 m

LED Engine	2700K	3000K	4000K
Eco Low Power [19W]	1530 lm	1680 lm	1790 lm
Eco Medium Power [31W]	2280 lm	2550 lm	2780 lm
Artist Low Power [19W]	1290 lm	1350 lm	1470 lm
Artist Medium Power [31W]	1930 lm	2060 lm	2160 lm


Wide Flood 50° Led Engine Eco, Medium Power

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	3550/1319	0.94 m
2 m	887/330	1.90 m
3 m	394/147	2.80 m
4 m	222/82	3.80 m

LED Engine	2700K	3000K	4000K
Eco Low Power [19W]	1440 lm	1580 lm	1680 lm
Eco Medium Power [31W]	2230 lm	2490 lm	2710 lm
Artist Low Power [19W]	1250 lm	1310 lm	1430 lm
Artist Medium Power [31W]	1910 lm	2040 lm	2140 lm




Optic Removal Tool for clear cover



Honeycomb Louvre



Prismatic Lens

W Snow White
W Snow WhiteW Snow White
B Jet BlackW Snow White
G Satin GoldS Radiant Silver
S Radiant SilverB Jet Black
B Jet BlackB Jet Black
G Satin Gold