

Beam Me Up-A4

Surface mounted luminaire - Wallwasher

Article code: 1MA4OWD-830M-D1200-W



Illustrations may only be similar and serve as an orientation.




Beam Me Up-A4. LED. Surface-mounted luminaire for ceilings with rebated diffuser set in a decorative ring. Luminaire head made of high-quality processed FRP (fiberglass reinforced plastic). Surface finish Snow White. Direct only light distribution with wide asymmetrical beam angle (Wallwasher). Color temperature: 3000K (Warm White). Color Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Reflector: Snow White. Single dimmed

0-10V. DxH (round). D=47,2". H=22,8"/10,6". Medium-power current. 8696lm. 104W. 44,1lbs. Binning initial <= MacAdam 3. IP20. Protection class I. cETLus. IK02. 120-277V. 50-60 Hz. RG0 (EN62471). A minimum LED lifetime of 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements. 5 years warranty. Manufacturer: Lightnet USA Inc

Beam Me Up-A4

Surface mounted luminaire - Wallwasher

Article code: 1MA4OWD-830M-D1200-W



Customer / Project: _____

Note: _____

Productname	Beam Me Up-A4
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Snow White
Light characteristics	Wallwasher
Color temperature	3000K
Color Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Reflector Color Inside	Reflector: Snow White
Control	Dimmable (0-10V)
Length L/Diameter D (in)	D=47,2"
Height H (in)	H=22,8"/10,6"
Current/Power	Medium-Power
Luminous Flux	8696lm
Power consumption	104W
Voltage	120-277V
Degree of protection	IP20
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
LED lifetime	L85/50,000h (tq 25°C)
Certification	cETLus
Weight (lbs)	44,1lbs

IP20

-120-277V

50-60 Hz

IK 02

RG0

≤3 MACADAM

L85/50000h

CE