
lightnet

Ringo Star-P1 Chandelier

Pendant luminaire - Direct/indirect light distribution

Article code: 1RP1OWE-827E-CW543-1500-K





Illustrations may only be similar and serve as an orientation.

Ringo Star-P1 Chandelier. LED. Pendant luminaire as chandelier designed with high lumen packages and decorative lighting effect. Three ring structure, each wrapped with a thread-like material. Surface finish Snow White. Direct/indirect light distribution. Color temperature: 2700K (Soft White). Color Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and uniform illumination. Switchable. D1=78,7''. D2=59,1''. D3=47,2''. W=3,9''. H=3,3''. White Curtain. Length of Curtain 59,1''. Cord suspension for parallel installation with power supply cable and canopy (Set). Pendant length max 158''. Power supply: transparent. Canopy: Matching luminaire`s surface color. Low-power current. lm on request. W on request. 139,6lbs. Binning initial <= MacAdam 3. IP20. Protection class I. cETLus. IK02. 120-277V. 50-60 Hz. RG0 (EN62471). A minimum LED lifetime of 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements. 5 years warranty. Manufacturer: Lightnet USA Inc

© LIGHTNET USA, INC | 2937 SW 27TH AVE STE 305 | MIAMI, FL 33133, Phone: (+1) 800-940-9092, E-Mail: info@lightnet.us, Internet: www.lightnet.us
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 30.01.2024

lightnet

Ringo Star-P1 Chandelier


Pendant luminaire - Direct/indirect light distribution


Article code: 1RP1OWE-827E-CW543-1500-K



Customer / Project:

Note:





Productname	Ringo Star-P1 Chandelier
Lamp	LED
Installation Type	Pendant luminaire
Surface finish	Snow White
Light characteristics	Direct/indirect light distribution
Color temperature	2700K
Color Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Switchable
D1 (in)	D1=78,7''
D2 (in)	D2=59,1''
D3 (in)	D3=47,2''
Width W (in)	W=3,9''
Height H (in)	H=3,3''
Current/Power	Low-Power
Luminous Flux	lm on request
Power consumption	W on request
Voltage	120-277V
Degree of protection	IP20
Suspension	Parallel cord susp (Set) Pendant length max 158''
Certification	cETLus
LED lifetime	L85/50,000h (tq 25°C)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (lbs)	139,6lbs

IP20 ~120-277V 50-60 Hz IK 02 RG0 ≤3 MacAdam L85/50000h CE ETL

© LIGHTNET USA, INC | 2937 SW 27TH AVE STE 305 | MIAMI, FL 33133, Phone: (+1) 800-940-9092, E-Mail: info@lightnet.us, Internet: www.lightnet.us
We reserve the right to make mistakes or modifications. Illustrations may only be similar and serve as an orientation. Kindly always check you are working with current version of mounting instruction.

Date: 30.01.2024