

Caleo-X4

Surface mounted luminaire - Direct/indirect light distribution Article code: 1AX4ASE-840M-L900-S



Illustrations may only be similar and serve as an orientation.


Caleo-X4. LED. Surface-mounted luminaire for walls and ceilings, tiered luminaire body made with 1" visible trim. Surface finish Radiant Silver. Direct light distribution and indirect lighting corona. Color temperature: 4000K (Cool White). Color Rendering Index (CRI): >80. Microprismatic screen for reduced luminance in office areas. UGR<=19. Reflector: Radiant Silver. Switchable. LxWxH (rectangular).

L=35,4". W=7,9". H=1"+1,4". Medium-power current. 3760lm. 31W. 10,6lbs. Binning initial <= MacAdam 3. IP20. Protection class I. cETLus. IK02. 120-277V. 50-60 Hz. RG0 (EN62471). A minimum LED lifetime of 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements. 5 years warranty. Manufacturer: Lightnet USA Inc

Caleo-X4

Surface mounted luminaire - Direct/indirect light distribution

Article code: 1AX4ASE-840M-L900-S



Customer / Project: _____

Note: _____

Productname	Caleo-X4
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Radiant Silver
Light characteristics	Direct/indirect light distribution
Color temperature	4000K
Color Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
UGR	UGR<=19
Reflector Color Inside	Reflector: Radiant Silver
Control	Switchable
Length L/Diameter D (in)	L=35,4"
Width W (in)	W=7,9"
Height H (in)	H=1"+1,4"
Current/Power	Medium-Power
Luminous Flux	3760lm
Power consumption	31W
Voltage	120-277V
Degree of protection	IP20
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
LED lifetime	L85/50,000h (tq 25°C)
Certification	cETLus
Weight (lbs)	10,6lbs

