

lightnet

Basic-A3

Surface mounted luminaire - Direct light distribution

Article code: 1BA3OWD-827H-D300-W



Illustrations may only be similar and serve as an orientation.





Basic-A3. LED. Surface-mounted luminaire for walls or ceilings. Surface finish Snow White. Direct only light distribution. Color temperature: 2700K (Soft White). Color Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and uniform illumination. Reflector: Snow White. Single dimmed 0-10V. DxH (round). D=11,8". H=2,3". High-power current. 1309lm. 13W. 6,4lbs. Binning initial <=

MacAdam 3. IP20. Protection class I. cETLus. IK02. 120-277V. 50-60 Hz. RG0 (EN62471). A minimum LED lifetime of 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements. 5 years warranty.

Manufacturer: Lightnet USA Inc

Basic-A3

Surface mounted luminaire - Direct light distribution



Article code: 1BA3OWD-827H-D300-W

Customer / Project: _____

Note: _____

Productname	Basic-A3
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Snow White
Light characteristics	Direct light distribution
Color temperature	2700K
Color Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Reflector Color Inside	Reflector: Snow White
Control	Dimmable (0-10V)
Length L/Diameter D (in)	D=11,8"
Height H (in)	H=2,3"
Current/Power	High-Power
Luminous Flux	1309lm
Power consumption	13W
Voltage	120-277V
Degree of protection	IP20
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
LED lifetime	L85/50,000h (tq 25°C)
Certification	cETLus
Weight (lbs)	6,4lbs

