

lightnet

Basic-P5

Pendant luminaire - Direct/indirect light distribution

Article code: 1BP5OWD-840M-D300-U



Illustrations may only be similar and serve as an orientation.




Basic-P5. LED. Pendant luminaire with minimal overall height of 1.5" without additional spacers. Direct/indirect light distribution. Opal diffuser for enhanced light transmission and uniform illumination. Surface finish Snow White. Single dimmed 0-10V. Color Rendering Index (CRI): >80. Color temperature: 4000K (Cool White). Medium-power current. DxH (round). D=11,8". H=1,5". Central cord suspension with canopy and power supply

cable (Set). Pendant length max 59". Power supply: transparent. Canopy: Matching luminaire`s surface color. 1220lm. 11W. Binning initial <= MacAdam 3. 7,5lbs. IP40. Protection class I. cETLus. IK02. 120-277V. 50-60 Hz. RG0 (EN62471). A minimum LED lifetime of 50,000h with 85% of lumen maintenance in 25°C ambient temperature, in compliance with IES LM-80 testing measurements. 5 years warranty. Manufacturer: Lightnet USA Inc

Basic-P5

Pendant luminaire - Direct/indirect light distribution

Article code: 1BP5OWD-840M-D300-U



D	D
mm	inch
300	11.75"
400	15.75"
500	19.625"
600	23.625"
800	31.5"

Customer / Project: _____

Note: _____

Productname	Basic-P5
Lamp	LED
Installation Type	Pendant luminaire
Light characteristics	Direct/indirect light distribution
Optical system	Opal diffuser
Surface finish	Snow White
Control	Dimmable (0-10V)
Color Rendering Index (CRI)	CRI>80
Color temperature	4000K
Current/Power	Medium-Power
Length L/Diameter D (in)	D=11,8"
Height H (in)	H=1,5"
Luminous Flux	1220lm
Power consumption	11W
Voltage	120-277V
Degree of protection	IP40
Suspension	Central cord susp. (Set) Pendant length max 59"
LED lifetime	L85/50,000h (tq 25°C)
Certification	cETLus
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (lbs)	7,5lbs

